

EQUIPMENT OUTLAY ITEMS				
No	Item	Specification	Quote	
1.	Video Conferencing Package	<ul style="list-style-type: none">• <u>11 units - Video Conferencing units</u> Technical Specification per Video Conferencing Units<ul style="list-style-type: none">- Rally Camera<ul style="list-style-type: none">- Ultra-HD imaging system supports: 4K, 1440p, 1080p, 900p, 720p, and SD at 30fps 1080p, 720p at 30 fps and 60 fps- Smooth motorized pan, tilt and zoom Pan: ±90° Tilt: +50° / -90° 15x HD zoom 90° field of view- Rally Display Hub<ul style="list-style-type: none">- Pickup range: 15 ft / 4.5m diameter Four microphones with eight beamforming elements- Mute button with LED status indicator- Captive cable: 9.6 ft (2.95m)- Rally Table Hub<ul style="list-style-type: none">- Single cable (CAT6A) connection to Rally Display Hub (16.4 ft (5m) CAT6A Ethernet cable included, supports customer-supplied cables up to 164 ft (50 m))- Active speaker detection: analyzes audio from up to 7 Mic Pods and 56 beams every 8ms- 12 Pin connector for Rally Mic Pod HDMI Type A for wired content sharing- HDMI Type A for display- Power input- USB Type C (Ultra HD / 4K capable)- USB Type A (reserved for future capability)- USB Type B (connects to meeting room computer) RJ45 (Ethernet)- Bluetooth® wireless technology- Rally Speaker (x2)<ul style="list-style-type: none">- High-performance 3" (76mm) driver- Patent pending suspension system eliminates vibration-induced camera shake and audio interference- Mini XLR cable (9.6 ft (2.95m)) connects to Rally Display Hub for both signal and power- Rally Mic Pod (x2)<ul style="list-style-type: none">- Pickup range: 15 ft / 4.5m diameter- Four microphones with eight beamforming elements- Mute button with LED status indicator- Captive cable: 9.6 ft (2.95m)- Remote control<ul style="list-style-type: none">- RF remote control (line of sight not required) CR2032 batteries (included)- USB Type C to USB Type C- USB Type A to USB Type B- CAT6A Ethernet cable- HDMI Type A (x2)	2,800,000	

		<ul style="list-style-type: none"> - A/C cables (x2) - Power Supplies (x2) - Mounting Kit - Documentation - RIGHTSENSE TECHNOLOGIES <ul style="list-style-type: none"> - RightLight with Wide Dynamic Range (WDR) - RightSight automatic camera control1 - RightSound Mic Matrix - RightSound Anti-Vibration Speakers ● <u>1 unit Meeting Room Touch Controller With Poe Connectivity</u> Technical Specification for 1 unit Room Touch Controller With Poe Connectivity <ul style="list-style-type: none"> - 10.1” diagonal screen touch screen with 1280 x 800 resolution - Touch: Capacitive, 10 points multi-touch - Power over Ethernet (PoE), IEEE 802.3af Type 1, - Class 3 device Ethernet: 10/100mbps - WiFi: 802.11a/b/g/n/ac - Bluetooth 5.0 - Integrated ultrasonic speaker - Integrated PIR Motion Sensor - Integrated accelerometer - Integrated ambient light sensor - 100 mm x 100 mm VESA FDMI - Internal cable retention and strain relief system ● <u>Complete package and ready-to-use</u> <ul style="list-style-type: none"> - <u>Free system installation per CMI and demonstration</u> - <u>User training</u> - <u>User manual</u> ● <u>Free delivery</u> 		
2.	Storage Server for ICT Hub	<ul style="list-style-type: none"> ● <u>Network Attached Storage Package</u> NAS Specification <ul style="list-style-type: none"> - CPU Model AMD Ryzen V1500B - CPU Quantity 1 - CPU Core 4 - CPU Architecture 64-bit - CPU Frequency 2.2 GHz - Hardware Encryption Engine - System Memory4 GB DDR4 ECC SODIMM - Memory Module Pre-installed 4 GB (4 GB x 1) - Total Memory Slots 2 - Maximum Memory Capacity 32 GB (16 GB x 2) ● <u>Storage Specification</u> 6 pcs Storage Drive <ul style="list-style-type: none"> - HDD Capacity : 2TB - Cache : 64MB - Speed : 7200rpm - Interface Type : SATA 3.0 	85,000	

		<ul style="list-style-type: none">- Size : 3.5"		
3.	75" Conference Room Interactive Screen	<ul style="list-style-type: none">● <u>Interactive Screen with Floor Stand Screen Bracket with rotatable wheel and Free Installation and delivery.</u>- UHD 4K display with resolution of 3840 × 2160.- Anti-glare and anti-blocking design to ensure smooth interaction.- Dual systems of Android and Windows (Optional with OPS) saving cost and easy to use, video conference software are recommended to run under Windows system.- Quick response, at most 50-points touch control and smooth writing experience.- Built-in network switch chip saves a network switch.- All-in-one design with tempered glass and intelligent temperature control, making it environmentally friendly and safety-guaranteed, support blue light protection. EDLA Certified <p>Interactive Specification Specification:</p> <ul style="list-style-type: none">- Screen Size: 75 inch to 86 inch- Backlight: DLED- Pixel Pitch: 0.14325(H) × 0.42975(V) mm- Resolution: 3840 × 2160 @60 Hz- Brightness: 400 cd/m² (Typ.)- Color Depth: 10 bit- Display Color; 1.07 G- Touch Type: Infrared Touch Screen- Touch Point: Up to 50-point multi-touch- Operation System: Android 13.0- Memory: 8 GB- Built-in Storage: 128 GB- Processor: Quad-core Cortex-A76 × 4 (2.4 GHz) and quad-core Cortex-A55 × 4 (1.8 GHz)- GPU: Mali-G610 MC4- HDCP Version: 2.3- Camera Pixel: Pixel 48MP for Photos & 8 MP for Video- Camera Function: Support intelligent switching between Android system, OPS, and PC.- Field Angle: 120°(diagonal), 110°(horizontal), 75°(vertical)- Distortion: ≤2.5%- Camera Resolution: RatioUp to 4K- Microphone specification: Omni-directional 8-array layout- Mic Function: Echo reduction and smart noise-cancellation- Voice Distance: 12 m- Sampling Rate: 32 K- Mic Depth: 16 bit- Loudspeaker: Built-in 2 × 20 W+25W loudspeaker;	230,000	

		<ul style="list-style-type: none"> - BluetoothBuilt-in: BLE (Bluetooth Low Energy) module supports Bluetooth 5.1 - NFC: Support screen mirroring by Android phones - Light Sensor: Yes - Video & Audio Input: HDMI In (HDMI 2.0) × 3, VGA In × 1, DP In (DP 1.2) × 1, Audio In × 1 - Video & audio output: HDMI Out (HDMI 2.0) × 1, Audio Out × 1, SPDIF Out × 1 - Control interface: TOUCH-USB 3.0 × 3, RS232 × 1 - Network Interface: LAN (1000 Mbps) × 2 WIFI AP & Station, 2.4G/5G WIFI 6, IEEE 802.11 a/b/g/n/ac/ax 2 × 2 MIMO (2.4 GHz and 5 GHz) authentication protocols WEP, WPA, WPA2, PSK and 802.1X EAP 		
4	Laptop	<ul style="list-style-type: none"> • Lenovo Legion 5i 16IRX9 83DG00DGPH 16inch WQXGA IPS 350nits 165Hz Core i7-14650HX 16GB RAM 1TB SSD RTX 4060 8GB WIN11, FREE DELIVERY 	120,000	
5	Photography and Video Camera	<ul style="list-style-type: none"> • <u>Photo and Video Camera with RF-S18-150mm f/3.5-6.3 IS STM Lens with Approx. 32.5MP APS-C CMOS sensor with 1.6x crop factor Up to 30 fps continuous shooting with AF/AE tracking 4K UHD Fine (7K oversampling), 4K 60p and Canon Log 3</u> <p>E-55 55mm Lens Cap LP-E6NH Lithium-Ion Battery (7.2V, 2130mAh) LC-E6 Charger for LP-E6 Battery Pack R-F-5 Camera Cover ER-R7 Camera Strap</p> <p>SPECIFICATION:</p> <p>AF Modes: One-Shot AF, Servo AF AF Point Selection: Spot AF, 1-point AF, Expand AF area (above/below/left/right or around), Flexible Zone AF 1 / 2 / 3, Whole area AF AF System Points: Up to 651 AF frame zones Built-in Flash Closest Focusing Distance (cm): 0.17 / 0.56 (AF, f=18-35mm) 0.12 / 0.39 (MF, f=18-24mm)</p> <p>Effective ISO: - Stills: 100–32,000 (H:51,200) - Movie: 100–12,800 - Canon Log movies: ISO 800–12,800 (L:100-640, H:16,000 - 25,600) - HDR PQ movies: ISO 100–12,800</p> <p>Effective Pixels (Megapixels): 32.5 Eye Detection AF: Human and Animal eye detection (All AF mode) Image Resolution: 6960×4640 (JPEG) L/RAW/C-RAW/HEIF) 4800×3200 (HEIF, JPEG M) 3472×2320 (HEIF, JPEG S1) 2400×1600 (HEIF, JPEG S2)</p>	120,000	

		<p>In-body Image Stabilizer (sensor-shift IS): Yes LCD Monitor (Size) (Inch): 3.0 Movie Digital IS: Yes Movie Format: MP4 Optical Image Stabilizer: Yes Viewfinder Type: 0.39-inch OLED, approx. 2.36million dots 59.94/119.88 fps Refresh Rate</p> <ul style="list-style-type: none">• FREE DELIVERY		
6	Drone	<ul style="list-style-type: none">• <u>Drone with Fly More Combo with Remote Control and microSD 64GB, package</u> <p>Drone Specification:</p> <ul style="list-style-type: none">- 3-Axis Gimbal with Tri-Camera System- 20MP 5.1K Wide-Angle 4/3 CMOS Hasselblad- 166mm 12MP 7x Zoom Telephoto- 70mm 48MP 3x Zoom Medium Telephoto Lens- Video is captured in 4K at 60 fps,- ISO Sensitivity Video 100 - 12800- Shutter speed - 1/8000 to 8 seconds- Internal Storage - 8 GB- GNSS Support - GPS, BeiDou, Galileo- Maximum Operating Distance - 9.3 Miles / 15 km- Operating Frequency<ul style="list-style-type: none">- 2.4 GHz (2.400 to 2.4835)- 5.8 GHz (5.725 to 5.850)- 7 Intelligent Flight Modes- Battery Capacity - 5000 mAh / 77 Wh- Battery Chemistry - Lithium-Ion- Up to 43 Minutes of Flight Time- O3+ Transmission with a 9.3-Mile Range- Omnidirectional Avoidance with APAS 5.0- D-LOG, D-LOG M & HLG Post Processing- Fly More Combo & RC Pro Remote- Drone Intelligent Flight Battery × 2- Drone 100W Battery Charging Hub × 1- Drone 65W Car Charger × 1- Drone Low-Noise Propellers (pair) × 3- Drone Convertible Carrying Bag × 1	160,000	
7	UPS	<ul style="list-style-type: none">• <u>Uninterruptible Power Supply with demonstration and user training.</u> <p>Specification:</p> <ul style="list-style-type: none">- On-Line 3000VA 2700W UPS- AC Surge Joule Rating: 625 J- Capacity: 3000 VA / 2700 W- Frequency Range: 40Hz ~ 70 Hz- Phase: Single phase with ground- Output Voltage: 208/220/230/240VAC- Output Power Factor: 0.9- AC Voltage Regulation: ±1% (Battery Mode)- Frequency Range: 47 ~ 53 Hz or 57 ~ 63 Hz (Synchronized Range)	80,000	

		<ul style="list-style-type: none">- Frequency Range (Battery Mode): 50 Hz ± 0.5% or 60Hz ±0.5%- Current Crest Ratio: 3:1- Waveform (Battery Mode): Pure Sinewave- AC Mode: 90%- Battery Type: 12 V / 9 AH- Battery Numbers: 6- Recharge Time: 4 hours recover to 90% capacity (Typical)- Charging Current: 1.0 A (max.)- Charging Voltage: 82.1 VDC ± 1%- Operation Humidity: 20–90% RH @ 0–40°C (non-condensing)- Noise Level: Less than 45dBA @ 1 Meter- What's in the box: 1x Vertiv Liebert GXT-3000MTPLUSC230, Quick Start Guide/User Manual, 1x Input Germany Power Cord, 1x Output Cable, USB Cable- Free delivery		
8	Portable Generator (5KW with accessories)	<ul style="list-style-type: none">● Portable Generator with accessories with user training. <p>Specification: Surge Output: 6100 W Rated Output: 5000 W Frequency: 60Hz Rated Voltage: 115/230V Receptacle: 1 x Twistlock 110/220V, 2 x Duplex 110V Phase: Single Phase DC 12V Output: Yes Rated Current: 21.7A Insulation Class:F Engine: 9.4HP DI Diesel Cylinder: 4-Stroke, Air-Cooled, Single Cylinder Starter: Electric Start Fuel Used: Diesel Fuel Capacity: 15L Low Oil Alert: Yes</p> <p>Accessories: High current extension cord 4 gangs (20A, 20 Meters)</p> <p>Free delivery User training</p>	80,000	
9	Conference Tables and Chairs	<ul style="list-style-type: none">- FREE DELIVERY	170,000	

No.	Semi-Expendable Items		
1.	1 DLSR Gimbal	<ul style="list-style-type: none">● <u>RS 4 Combo Gimbal Stabilizer Package</u>- <u>Free Delivery</u> <p>Camera Gimbal Specification</p> <ul style="list-style-type: none">- Max Payload: 3 kg (6.6 lbs)- Axis Locks: 2nd-Gen Automated Axis Locks- Axis Arm Material: Carbon Fiber or Aluminum Alloy- Fine-Tuning Knob: Yes- 1.8" OLED Full-Color Touchscreen- 4th-Gen RS Stabilization Algorithm- Joystick Mode: Zoom/Gimbal Control- 2nd-Gen Native Vertical Shooting- Battery Design: Detachable- RSA Communication Port- Extensive Control Ecosystem- Teflon™-Coated Axis Arms- Max Battery Runtime: 29.5 Hours <p>Package Inclusion</p> <ul style="list-style-type: none">- Gimbal × 1- BG21 Battery Grip × 1- Quick-Release Plate (Arca-Swiss/Manfrotto) × 1- Extended Grip/Tripod (Plastic) × 1- Lens-Fastening Support × 1- USB-C Charging Cable (40 cm)× 1- Multi-Camera Control Cable (USB-C, 30 cm)× 1- Screw Kit × 1- Logo Sticker × 1- Briefcase Handle × 1- USB-C Charging Cable (40 cm) × 1- Carrying Case × 1- Focus Pro Motor × 1- Focus Pro Motor Rod Mount Kit × 1- FIZ Sticker × 1- Focus Gear Strip × 1	45,000
2.	1 Wireless Mic for DLSR	<ul style="list-style-type: none">● <u>Wireless Mic for Camera (2TX,1 RX and Charging Case)</u>- High-Quality Audio RecordingAll-In-One, Ready to Use- 14-Hour Internal Recording- 32-bit Float Internal Recording- Intelligent Noise Cancelling,- Crystal-Clear Vocals250m (820 ft.) Range- Single-Charge Battery Life: 6 hours- Max Battery with Charging Case: 18 hours- TX Direct Bluetooth Connection- Touch Screen Dial- Free delivery <p>Transmitter Specification</p> <ul style="list-style-type: none">- Dimensions 46.06×30.96×21.83 mm (L×W×H)- Weight 28 g- Wireless Mode GFSK 1 Mbps and 2 Mbps	25,000

		<ul style="list-style-type: none">- Equivalent Isotropic Radiated Power (EIRP) <20 dBm- Wireless Mode Operating Frequency 2.400-2.4835 GHz- Bluetooth Protocol BR/EDR- Bluetooth Operating Frequency 2.400-2.4835 GHz- Battery Type Li-ion- Battery Capacity 360 mAh- Battery Energy 1.39 Wh- Battery Voltage 3.87 V <p>Receiver Specification</p> <ul style="list-style-type: none">- Dimensions 54.20×28.36×22.49 mm (L×W×H)- Weight 28 g- Wireless Mode GFSK 1 Mbps and 2Mbps- Equivalent Isotropic Radiated Power (EIRP) <20 dBm- Operating Frequency 2.400-2.4835 GHz- Battery Type Li-ion- Battery Capacity 360 mAh- <p>Charging Case Specification</p> <ul style="list-style-type: none">- Weight 200 g- Battery Type 18650 Li-ion- Battery Capacity 3250 mAh- Battery Energy 11.7 Wh- Battery Voltage 3.6 V- Charging Specification 5 V, 1.5-3 <p>Inside the Box</p> <ul style="list-style-type: none">● Receiver● Transmitter (Shadow Black) x2● Charging Case● Carrying Bag● Clip Magnet x2● Mobile Phone Adapter● Windscreen x2● Camera Audio Cable● USB-C Cable	
3.	3 Wireless Microphones for the ICT Hub	<ul style="list-style-type: none">● <u>Wireless Microphone System Professional at least 3-Channel (or more) UHF Wireless Mic Fixed Frequency Metal Cordless Mic with at least 3 Handheld Dynamic Microphones or more.</u> <p>Specification:</p> <ul style="list-style-type: none">- Auto-scan function to locate the best frequency nearby.- Crystal clear audio quality with cardioid pickup pattern to minimize noise.- Sturdy all-metal construction for both receivers and handheld mics.- Rack-mountable with built-in rack ears for easy operation.- 4 XLR outputs for each channel and one 1/4" TS unbalanced mixed output for combined audio.- Dynamic range: >105dB- Frequency response: 50Hz - 18kHz- Up to 260ft long operation range.- > 8 hours battery life for each transmitter.	15,000

		<ul style="list-style-type: none">- Fixed frequency design in the 500MHz UHF frequency band. The frequency for this system is 541.9MHz, 546.3MHz, 561.6MHz, and 568.65MHz.- Style : Handheld Microphone- Audio input level: Gain:0dB; -20 dBV maximum-10dB; -0 dBV maximum- Power requirement: 2 AA size alkaline batteries for each transmitter- Power requirement: DC 12 – 15V, Current 1000mA,- External power adapter- Free delivery	
4.	Remote Internet Connectivity Package	<ul style="list-style-type: none">● <u>Satellite Internet connectivity device package with installation and demonstration. Free delivery</u> <p>Specification</p> <p>Wireless LAN Standards: IEEE 802.11b, IEEE 802.11g, IEEE 802.11ac, IEEE 802.11n, IEEE 802.11a</p> <p>Antenna: Electronic Phased Array</p> <p>Orientation/Direction: Motorized Self Orienting</p> <p>Environmental Rating: IP54</p> <p>Snow Melt Capability: Up to 40mm / hour (1.5in / hour)</p> <p>Operating Temperature: -30°C to 50°C (-22°F to 122°F)</p> <p>Field of View: 110 °</p> <p>Average Power Usage: 50-75W</p> <p>Dish Weight: 2.9kg without cable, 4.2kg with 22.9m cable</p> <p>Wi-Fi Technology” IEEE 802.11a/b/g/n/ac standards</p> <p>Router Generation: WiFi: 802.11ac (Wi-Fi 5)</p> <p>Radio: Dual Band - 3 x 3 MIMO</p> <p>Security: WPA2</p> <p>Environmental Rating: IP54, configured for indoor use</p> <p>Coverage: Up to 185m² (2000sqft)</p> <p>Operating Temperature: -30°C to 50°C (-22°F to 122°F)</p> <p>Device Connectivity: Supports up to 128 devices</p> <p>Ethernet Adapter.</p>	38,000
5.	1 Portable Power Supply	<ul style="list-style-type: none">● <u>Portable Power Station (700W)</u> <p>-700W AC Pure Sine Wave Inverter (1,400W Surge)</p> <p>- 537Wh Capacity</p> <p>- LifePO4 Battery with 2,500+ Life Cycles to 80%</p> <p>- 13 Outputs For Multiple Devices</p> <p>- 6 Ways to Recharge (AC/Solar/Car/Generator/AC+Solar/Dual AC)</p> <p>- 200W Max. Solar Input</p> <p>- 400W Max. Fast Dual Charging (Solar + AC Adapter Simultaneously)</p> <ul style="list-style-type: none">● FREE DELIVERY	34,000